

PREMIER

ITP-80 Portable



Model	ITP-80 Portable BT	ITP-80 Portable WF
Color:	Black	
Printing method:	Direct thermal	
Resolution:	203 DPI	
Line spacing:	3.75 mm (Adjustable by commands)	
Print width:	72 mm	
Max. print speed:	Max. 70 mm/s	
Media roll diameter:	Max. 50 mm	
Interfaces:	USB + Bluetooth (1+1)	USB + Wifi (1+1)
Input buffer:	128 Kbytes	
Nv Flash:	4M Kbytes	
Emulation:	ESC/POS	
Character size:	ANK, Font A: 1.5×3.0 mm (12×24 dots) Font B: 1.1×2.1 mm (9×17 dots) simplified/traditional Chinese: 3.0×3.0 mm (24×24 dots)	
Barcode types:	1D: UPC-A/UPC-E/JAN13 (EAN13) / JAN8 (EAN8) / CODE39/ITF/CODABAR/CODE93/CODE128; 2D: QRCODE	
Extended character sheet:	PC347 (Standard Europe) / Katakana / PC850 (Multilingual) / PC860 (Portuguese) / PC863 (Canadian-French) / PC865 (Nordic) / West Europe / Greek / Hebrew / East Europe / Iran / WPC1252 / PC866 (Cyrillic#2) / PC852 (Latin2) / PC858 / IranII / Latvian / Arabic / PT151 (1251)	
Rotation:	0°, 90°, 180°, 270°	
Dimensions:	135 x 105 x 61.5 mm (LxWxH)	
Weight:	0.3 Kg	
Printer head life:	50 Km	
Systems:	Windows/Android/iOS/Linux	
Battery:	7.4V/ 2000mAh	
Charging input:	DC 5V/2A	
Work environment:	0~45°C, 10~80% RH no condensing	
Storage environment:	-10~60°C, ≤10~90% RH no condensing	