

Promag PCR300 and PCR330 are desktop rfid readers which can be used for system logon / logoff, operator identification and many other desktop rfid applications.

PCR300 series readers are available in several versions depending which card technology, casing, interface and output you require:

- | | |
|-----------------|--|
| Card Technology | <ul style="list-style-type: none">• 125Khz RFID• 13.56MHz MIFARE® |
| Case Types | <ul style="list-style-type: none">• Cradle slot casing• Flat casing |
| Interfaces | <ul style="list-style-type: none">• USB Keyboard Emulation• USB HID• RS232 |
| Output | <ul style="list-style-type: none">• Decimal• Hexadecimal |



Flat Casing



Cradle Slot Casing

Cradle slot is designed to accept RFID card as below:

System Unlocked - System can be used when the registered card is sitting in the cradle slot.

System Locked - System cannot be used when the registered card is removed from the cradle slot.

Features

- Compact design
- 125kHz RFID or 13.56MHz MIFARE
- USB keyboard emulation, USB virtual COM or RS232
- Different casing options

Also available

WinLoq - PC logon/logoff software and reader

| | |
|---------------------|--|
| Frequency | 125Khz RFID or 13.56MHz MIFARE |
| Case type | Cradle slot or Flat |
| Interface | USB Keyboard, USB Virtual COM or RS232 |
| Baud Rate | 9600, No Parity, 8 data bits, 1 stop bit |
| Output | Decimal or Hexadecimal (option) |
| Power Supply | DC 5V, 200mA |
| Dimensions | 65 x 100 x 23mm (W x H x D) |
| Mounting | Desktop |
| Temperature | 0°C ~ +55°C |